



Frutteto³ Classic

60_70_80
80.4_90_100

Frutteto³

- SDF SERIES 1000 TIER III ENGINES, 3 OR 4 CYLINDERS, TURBO OR TURBO INTERCOOLER, WITH ELECTRONIC ENGINE MANAGEMENT
- POSSIBILITY TO ADJUST ENGINE SPEEDS AND SAVE THEM TO MEMORY AT THE PRESS OF A BUTTON
- SYNCHRO GEARBOX, 20 FWD + 10 REV, 30 FWD + 15 REV ECO
- MAXIMUM SPEED 40 KM/H
- ALL-WHEEL BRAKING WITH OIL-BATH DISCS AND HYDROSTATIC CONTROL
- HYDROSTATIC STEERING WITH INDEPENDENT HYDRAULIC SYSTEM
- 540/540 ECO/1000 AND GROUNDSPEED PTO

SAME
Rely on us.

TECHNICAL DATA

Version	FRUTTETO ³ Classic 60	FRUTTETO ³ Classic 70	FRUTTETO ³ Classic 80	FRUTTETO ³ Classic 80.4	FRUTTETO ³ Classic 90	FRUTTETO ³ Classic 100	
	4WD	4WD	4WD	4WD	4WD	4WD	
ENGINE	SDF 1000.3 WT TIER III						SDF 1000.4 WT TIER III
Cylinders/Displacement	no/cm ³ 3/3000						4/4000
Aspiration	Turbo Intercooler						Turbo Intercooler
Max. homologated power (2000/25/CE)	HP/kW 62/46						80/59
Rated engine speed	rpm 2200						2200
Max. torque	Nm 240						325
Max. torque engine speed	rpm 1600						1600
Cooling	liquid-oil						
Engine control	electronic						
Air cleaner	dry with safety cartridge and dust ejector						
Silencer underhood	with downswept exhaust under platform						
Fuel tank capacity	litres						55
DIMENSIONS AND WEIGHTS (with rear tyres)	360/70R24		360/70R24		380/70R24		380/70R24
Max. length without link arms	mm 3186		3186		3208		3338
Min. - max. width	mm 1443-2012		1443-2012		1478-1988		1478-1988
Max. height at safety frame	mm 2228		2228		2380		2380
Max. height at engine hood	mm 1138		1138		1138		1138
Max. height at steering wheel	mm 1148		1148		1148		1148
Ground clearance	mm 225		225		225		225
Wheelbase	mm 1990		1990		2120		2120
Front track min. - max.	mm 1165-1442		1165-1442		1165-1442		1165-1442
Rear track min. - max.	mm 1083-1652		1083-1652		1058-1608		1165-1442
Minimum steering radius without braking	mm 3900		3900		4000		4000
Weight with safety frame	kg 2250		2400		2400		2650

TRANSMISSION	
Gearbox clutch	mechanically operated
Mechanical gearbox, 5 synchronised gears, 2 gear ranges with underdrive (Min. speed: 1.33 km/h)	20 FWD + 10 REV
Mechanical gearbox, 5 synchronised gears, 2 gear ranges with underdrive and creeper (Min. speed: 0.21 km/h)	30 FWD + 15 REV
Max. speed	km/h 40
Shuttle	mechanical, synchronised
Rear differential lock	mechanically operated
Lubrication	forced
BRAKES AND STEERING	
Braking system	four wheel braking, discs in oil bath on all 4 wheels, hydrostatically operated
Parking brake	independent
Trailer braking	hydraulic braking valve
Hydrostatic steering	independent pump
Steering angle	60°
FRONT AXLE	
Drive and differential engagement	mechanically operated
Front differential lock	mechanically operated

REAR P.T.O.	
Clutch	dry, independent operated
Speed	rpm 540-540 ECON
	rpm 540-540 ECON-1000
	rpm 540-540 ECON + synchro
Operation	mechanical, independent
HYDRAULIC LIFT	
Rear hitch	mechanical
Maximum lifting capacity	kg 3000
Pump output	l/min. 45
Auxiliary hydraulic control valves	no. ways 4/6
3 point linkage (link arms and top link)	fixed hitching balls quick attach claw links
RH link arm and stabilisers	mechanical
DRIVING POSITION	
Gears levers	lateral
Rops	fixed folding
Instruments	analog with Check-Panel
Driver's seat	mechanical adjustment with safety belt

30 FWD + 15 REV GEARBOX WITH UNDERDRIVE AND CREEPER - SPEED IN KM/H AT ENGINE SPEED OF 2200 RPM WITH 380/70 R 24 REAR TYRES

1 SR min	2 SR min	3 SR min	4 SR min	5 SR min	1 M min	2 M min	3 M min	4 M min	5 M min	1 V min	2 V min	3 V min	4 V min	5 V min
0,21	0,31	0,43	0,60	0,84	1,33	1,91	2,73	3,82	5,32	7,35	10,51	15,06	21,04	29,27
1 SR	2 SR	3 SR	4 SR	5 SR	1 M	2 M	3 M	4 M	5 M	1 V	2 V	3 V	4 V	5 V
0,27	0,36	0,52	0,73	1,02	1,62	2,31	3,32	4,64	6,45	8,93	12,75	18,28	25,54	40,00*

The above specifications refer to tractors with all available equipment. For standard equipment and options, refer to the current price list and ask your local dealer for details.

*=MAX. SPEED EFFECTIVE
PLEASE NOTE: REVERSE SPEEDS ARE SLIGHTLY LOWER THAN THE CORRESPONDING FORWARD SPEEDS
REVERSE SPEED ARE SLIGHTLY LOWER THAN THE CORRESPONDING FORWARD SPEEDS WITHOUT UNDERDRIVE.

DEALER CONTACT

SAME
Rely on us.

We recommend the use of SDF Lubricants and Coolant 

Company with Quality System Certified in compliance with ISO 9001:2000

SAME DEUTZ-FAHR GROUP S.p.A. _ Viale Cassani, 14 _ 24047 _ Treviglio (BG) _ Italy _ Ph: +39 0363 4211 _ www.samedeutz-fahr.com

SAME DEUTZ-FAHR U.K. LTD. _ Barby Lane, Barby, Nr Rugby _ CV23 8TD _ WARWICKSHIRE _ UK _ www.same-tractors.com