



"I want a tractor that is useful in a variety of situations."

"My tractor must be productive, compact and comfortable."



FRUTTETO³ Natural

50 | 55 | 65 | 75

The perfect compromise between productivity and reliability.

SAME Frutteto³ Natural is the perfect combination of simplicity and strength, a compact multi-functional tractor with power from 50 to 75 Hp, 2WD or 4WD.

Thanks to its reduced dimensions and the robustness of its components, the SAME Frutteto³ Natural is ideal both for specialised crops and open field work. The reliable and tested 1000 Series SDF engines ensure long life with low operating costs.



SAME

FRUTTETO ³ Natural		50	55	65	75
ENGINE					
Emissions		Tier3	Tier3	Tier3	Tier3
Manufacturer		SDF 1000.3 W	SDF 1000.3 WT	SDF 1000.3 WT	SDF 1000.3 WT1
Cylinders/Capacity	No./cc	3/3000	3/3000	3/3000	3/3000
Naturally aspirated		●	-	-	-
Turbocharged intake		-	●	●	-
Turbo Intercooler intake		-	-	-	●
Max. homologated power (ECE R 120)	kW/hp	34.4/47	36.8/50	46/62	53/72
Max. engine speed (rated)	rpm	2,200	2,200	2,200	2,200
Max. torque	Nm	172	213	240	265
Engine control mechanical		●	●	●	●
Cyclone pre-filter		○	○	○	○
Cooling liquid		●	●	●	●
Under-hood silencer with side exhaust		●	●	●	●
Fuel tank capacity	litres	65	65	65	65
Biodiesel fuel	%	B100	B100	B100	B100
MECHANICAL GEARBOX					
Synchronised		●	●	●	●
Number of speeds	n°	8+2	8+2	8+2	8+2
Number of speeds with supercreeper gear	n°	12+3	12+3	12+3	12+3
Minimum/maximum speed with supercreeper gear	km/h	2.4/0.38	2.4/0.38	2.4/0.38	2.4/0.38
Max. speed	km/h	30	30	30	30
Mechanical clutch dry, single		●	●	●	●
REAR PTO					
Mechanical clutch dry, single		●	●	●	●
Mechanical engagement		●	●	●	●
PTO 540		●	●	●	●
P.T.O. 540/540ECO		○	○	○	○
FRONT AND REAR AXLE					
Front wheel drive mechanically engaged (for 4WD versions only)		●	●	●	●
Mechanically operated differential lock		●	●	●	●
Steering angle/radius 2WD	degrees/mm	70°/3,390	70°/3,390	70°/3,390	70°/3,390
Steering angle/radius 4WD	degrees/mm	55°/4,680	55°/4,680	55°/4,680	55°/4,680
BRAKES					
Braking system with wet brake discs		●	●	●	●
Mechanical parking brake		●	●	●	●
STEERING					
Hydrostatic steering with independent pump		●	●	●	●
Steering pump delivery	l/min	18	18	18	18
HITCH					
Category		II	II	II	II
Rear hitch mechanical		●	●	●	●
Rear hitch lift capacity	kg	2845	2845	2845	2845
HYDRAULIC SYSTEM					
Pump output (std)	l/min	31	31	31	31
Pump output (opt)	l/min	42	42	42	42
Open-centre hydraulic system		●	●	●	●
Mechanical distributor engagement		●	●	●	●
Rear auxiliary distributors	No. of ways	2 / 4	2 / 4	2 / 4	2 / 4
DRIVING POSITION					
Side control levers		●	●	●	●
Folding front roll bar		●	●	●	●
Driver seat with mechanical suspension		●	●	●	●
Instrumentation analogue		●	●	●	●
DIMENSIONS AND WEIGHTS					
Standard rear tyres		380/70R24	380/70R24	380/70R24	380/70R24
Max. length with rear linkage	mm	3531	3531	3531	3531
Max length. with rear linkage and roll bar folded down	mm	3768	3768	3768	3768
Width	mm	1538	1538	1538	1538
Wheelbase (4WD/2WD)	mm	1996/2042	1996/2042	1996/2042	1996/2042
Front track (4WD/2WD)	mm	1297/1354	1297/1354	1297/1354	1297/1354
Rear track	mm	1221	1221	1221	1221
Max. height with roll bar folded down	mm	2372	2372	2372	2372
Max. height at hood	mm	1468	1468	1468	1468
Weight (4WD/2WD)	kg	2550/2450	2550/2450	2600/2500	2650/2550
Maximum load capacity (4WD/2WD)	kg	4800/3800	4800/3800	4800/3800	4800/3800

STD ● OPT ○

DEALER

Use of original SDF lubricants and coolants is recommended.



SAME is a brand of
same-tractors.com



SAME